

CLAMP COUPLINGS

The Clamp couplings are used in the food, oenology and pharmaceutical sector. These are quick couplings of manual disconnection where the ends are symmetrical. Depending on the measurements, there are two types: millimeter clamp coupling and inch clamp coupling.

MATERIALS

SS316

SS304


TRI CLAMP FOR HOSE SS316



CODE FIC197

ø Shank mm	ø Exterior plate	ø Shank mm	ø Exterior plate	ø Shank mm	ø Exterior plate
10	25	12	50	63	77
12	25	16	50	63	91
16	25	19	50	76	91
19	25	25	50	76	106
10	34	32	50	101	119
12	34	38	50		
16	34	50	50		
19	34	38	64		
25	34	51	64		
10	50	50	77		


CLAMP FERRULE FOR WELDING BS "3A" SS316



CODE FIC190

ND	A mm	B mm	C mm	D mm
1/2"	9,4	12,7	25,2	28,6
3/4"	15,75	19,05	25,2	28,6
1"	22,2	25,4	50,5	28,6
1 1/4"	28,5	31,8	50,5	28,6
1 1/2"	34,8	38,1	50,5	28,6
2"	47,5	50,8	64	28,6
2 1/2"	60,2	63,5	77,5	28,6
3"	72,9	76,2	91	28,6
4"	97,4	101,6	119	28,6


CLAMP FERRULE FOR WELDING DIN SS316



CODE FIC190

ND	A mm	B mm	C mm	D mm
15	15	18	34	18
20	19	22	34	18
25	25	28	50,4	21,5
32	31	34	50,4	21,5
40	37	40	50,4	21,5
50	49	52	64	21,5
65	66	70	90,9	28
80	81	85	106	28
100	100	104	118,8	28

CLAMP SS304



CODE FIC191

BS	DIN 32676	C mm
1/2" - 3/4"	-	25,2
-	10-15-20	34
1" - 1 1/2"	25-32-40	50,4
2"	50	64
2 1/2"	-	77,5
3"	65	90,9
-	80	106
4"	100	119

TECNIMAN

Camino del fus, 59 • 46470 Massanassa (Valencia - Spain)
P. +34 96 125 30 55 • Fax +34 96 125 00 45 • info@tecniman.es • www.tecniman.es

CLAMP CAP DIN SS316



ND	A mm	B mm
10-15-20	34	5
25-32-40	50,4	6,3
50	64	6,3
65	91	6,3
80	106	6,3
100	119	7,9

CODE FIC193

CLAMP CAP BS "3A" SS316



ND	A mm	B mm
1/2" - 3/4"	25,2	5
1" - 1 1/2"	50,4	6,3
2"	64	6,3
2 1/2"	77,5	6,3
3"	91	6,3
4"	119	7,9

CODE FIC193

CLAMP SEAL BS



ND	B1 mm	B2 mm
1/2"	21,8	9,4
3/4"	21,8	15,7
1"	50,4	22,1
1 1/4"	50,4	-
1 1/2"	50,4	34,8
2"	64	47,5
2 1/2"	77,5	60,2
3"	91	72,8
4"	119	97,6

CODE
EPDM FIC19200BS
PTFE FIC19201BS
Silicone FIC19202BS
Viton FIC19203BS
NBR FIC19204BS

CLAMP SEAL DIN



ND	B1 mm	B2 mm
15	34	16,2
20	34	20,2
25	50,4	26,2
32	50,4	32,2
40	50,4	38,2
50	64	50,2
65	90,9	66,2
80	106	81,2
100	118,8	100,2

CODE
EPDM FIC19200DIN
PTFE FIC19201DIN
Silicone FIC19202DIN
Viton FIC19203DIN
NBR FIC19204DIN