

CLAMPS AND FLANGES

SUPRA CLAM



CODE
Zinc plated steel FA563
Stainless steel FA564

Ø mm
17-19
19-21
21-23
23-25
25-27
27-29
29-31
31-34
34-37
37-40
40-43
43-47
47-51
51-55
55-59
59-63
63-68
68-73
73-79
79-85
85-91
91-97
97-104
104-112
112-121
121-130
130-140
140-150
150-162
162-174
174-187
187-200
200-213
213-226
226-239
239-252
252-265
265-278

ASFA CLAMP



CODE
Zinc plated steel FA5650
Stainless steel FA5654

Ø mm
8-12
8-16
12-22
16-27
20-32
25-40
30-45
32-50
40-60
50-70
60-80
70-90
80-100
90-110
100-120
110-130
120-140
130-150
140-160
150-170
160-180
170-190
180-200
190-210
200-220
210-230
220-240
230-250
250-270
260-280
270-290
280-300
290-310
300-320

MATERIALS Zinc plated steel and Stainless steel.

MATERIALS Zinc plated steel and Stainless steel.

2 EAR CLAMP



CODE

Zinc plated steel FA5825

Stainless steel FA5826

ø mm
5-7
7-9
9-11
11-13
13-15
15-18
17-20
18-21
20-23
22-25
23-27
25-28
28-31
31-34
34-37
37-40
40-43
43-46

MATERIALS Zinc plated steel and Stainless steel.

GROOVED CABLE TIES



CODE

White FA571

Black FA572

Width mm	Length mm	Colours	Quantity
2,5	160	Blanco/Negro	100
2,5	200	Blanco/Negro	100
3,6	140	Blanco/Negro	100
3,6	200	Blanco/Negro	100
4,8	200	Blanco/Negro	100
4,8	300	Blanco/Negro	100
7,6	430	Blanco/Negro	100
7,6	450	Blanco/Negro	100
7,6	750	Blanco/Negro	100

MATERIALS Nylon

SAFETY CLAMP WITH PIN DIN 2817 ALUMINUM



CODE

Aluminum CG531805

DN mm	Working pressure bar	ø Hose mm	ø ext. MIN-MAX mm
25	25	25x6	36-39
32	25	32x6	43-46
38	25	38x6,5	50-53
50	25	50x8	63-67
65	25	65x7	78-82
75	25	75x8	89-93
100	25	100x8	114-119

NOTE Other figures available upon request.

SAFETY CLAMP DIN 2817 ALUMINUM



CODE CG53180K



CODE Aluminum blue CG53180K1



CODE Aluminum red CG53180K2



CODE Aluminum black CG53180K3



CODE Aluminum white CG53180K4



CODE Aluminum yellow CG53180K5

DN mm	Working pressure bar	ø Hose mm	ø ext. MIN-MAX mm	Screw
13	25	13x5	22-24	M6X20
19	25	19x6	30-33	M6X20
25	25	25x5	34-36	M6X20
25	25	25x6	36-39	M6X20
25	25	25x8	40-43	M6X20
32	25	32x5	41-43	M6X20
32	25	32x6	43-46	M6X20
32	25	32x8	47-50	M6X20
32	25	32x5	47-49	M6X20
38	25	38x6,5	50-53	M6X20
38	25	38x8	53-56	M6X20
38	25	38x10	57-60	M6X20
40	25	40x7	53-56	M6X20
40	25	40x10	58-61	M6X20
45	25	45x7	58-61	M8X25
50	25	50x5	59-61	M8X25
50	25	50x6	61-63	M8X25
50	25	50x8	63-67	M8X25
50	25	50x10	69-71	M8X25
63	25	63x6	74-76	M8X25
63	25	63x8	78-82	M8X25
63	25	63x10	84-87	M8X25
75	25	75x6	85-89	M8X25
75	25	75x8	89-93	M8X25
75	25	75x10	94-97	M8X25
75	25	75x12	98-101	M8X25
80	25	80x8	94-97	M8X25
90	25	90x6,5	101-105	M8X25
100	25	100x6,5	111-115	M10X40
100	25	100x8	114-119	M10X40
100	25	100x10	118-122	M10X40
100	25	100x12	122-126	M10X40
100	25	100x14	126-130	M10X40
125	25	125x10	143-148	M10X60
150	16	150x10	168-174	M12X60
200	16	200x12	222-229	M12X50

SAFETY CLAMP DIN 2817 AISI 316

CODE
Stainless steel CG53180L

DN mm	Working pressure bar	ø Hose mm	ø ext. MIN-MAX mm	Screw
13	25	13x5	22-24	M6X20
19	25	19x6	30-33	M6X20
25	25	25x6	36-39	M6X20
32	25	32x6	43-46	M6X20
38	25	38x6,5	50-53	M6X20
38	25	38x8	53-56	M6X20
50	25	50x6	61-63	M8X25
50	25	50x8	63-67	M8X25
50	25	50x10	69-71	M8X25
63	25	63x8	78-82	M8X25
75	25	75x8	89-93	M8X25
100	25	100x8	114-119	M10X40
100	25	100x10	118-122	M10X40

NOTE Clamps also available in brass (CG5318B) and blue polypropylene (CG5318P1), red (CG5318P2), black (CG5318P3) and white (CG5318P4).