

# COMPRESAIR-20

Hoses for aeration



## CHARACTERISTICS

Black rubber hose manufactured in a continuous process, with an intertwined synthetic textile braid. Excellent flexibility. Resistant to ageing, weather and severe conditions of use.

## APPLICATIONS

Ideal hose for a compressed air conduit, public work and industrial use. Especially suitable for equipping pneumatic tools.

## TEMPERATURES

From -20°C to +80°C

| ø Interior mm | ø Exterior mm | Weight kg/m | Working pressure bar | Burst pressure bar | Roll m | Code        |
|---------------|---------------|-------------|----------------------|--------------------|--------|-------------|
| 6             | 13            | 0,18        | 20                   | 60                 | 100    | AP979006013 |
| 8             | 15            | 0,22        | 20                   | 60                 | 100    | AP979008016 |
| 10            | 17            | 0,23        | 20                   | 60                 | 100    | AP979010017 |
| 13            | 20            | 0,41        | 20                   | 60                 | 100    | AP979013023 |
| 16            | 25            | 0,46        | 20                   | 60                 | 100    | AP979016026 |
| 19            | 29            | 0,64        | 20                   | 60                 | 50/20  | AP979019029 |
| 25            | 35            | 0,80        | 20                   | 60                 | 50     | AP979025036 |