

RACORES DIN 11851 NW

Los racores inoxidable NW se fabrican según norma DIN 11851, idóneos para su uso en industria alimentaria, química y farmacéutica. La rosca cumple norma DIN 405/1.

MATERIALES

SS316

SS304

DIN 11851 - MALE WELD



CODE CB271

ND
15
20
25
32
40
50
65
80
100

DIN 11851 - CAP WELD



CODE CB272

ND
15
20
25
32
40
50
65
80
100

DIN 11851 - MALE WITH SMOOTH SHANK AND SAFETY RING



CODE FIC1131

ND	Shank mm
15	13
20	19
25	25
32	32
40	38
40	40
50	50
65	63
80	75
100	100

DIN 11851 - CAP WITH SERRATED SHANK AND SAFETY RING



CODE FIC1121

ND	Shank mm
15	13
20	19
25	25
32	32
40	38
40	40
50	50
65	63
80	75
100	100

DIN 11851 - CAP WITH SMOOTH SHANK AND SAFETY RING



CODE FIC1130

ND	Shank mm
15	13
20	19
25	25
32	32
40	38
40	40
50	50
65	63
80	75
100	100

DIN 11851 - CAP WITH SERRATED SHANK AND SAFETY RING



CODE FIC1120

ND	Shank mm
15	13
20	19
25	25
32	32
40	38
40	40
50	50
65	63
80	75
100	100

DIN 11851 – WELD SHANK WITH SAFETY RING



CODE CB249A

di x dE	Shank mm
28,5 x 33,7	25
37,2 x 42,4	32
43,1 x 48,3	38
54,5 x 60,3	50
70,3 x 76,1	63
82,5 x 88,9	75
107,1 x 114,3	100
159,3 x 168,3	150
208,9 x 219,1	200

DIN 11851 – SCREW



CODE CB273

ND
15
20
25
32
40
50
65
80
100

DIN 11851 – CAP NUT SS304 WITH PIVOT



CODE CB276

ND
15
20
25
30
40
50
65
80
100

DIN 11851 – MALE THREAD CAP



CODE CB279

ND
20
25
32
40
50
65
80
100

DIN 11851 – NUT WITH VIEWER



CODE CB280

ND
25
32
40
50
65
80
100

DIN 11851 – NW LIP SEALS FOR MALE NW

LIP FOR MALE NW



CODE
EPDM CB2740
NBR CB2748
Viton CB2749
Flat for silicone nut CB2752

ND
15
20
25
32
40
50
65
80
100

NOTA On request, other types of DIN 11851 fittings can be supplied, such as elbows, reducers, converters, etc.

