

# HYDROCARBON PUMPING 15 BAR

Hoses



## CHARACTERISTICS

Hose of black NBR rubber constructed around a mandrel with intertwined textile reinforcement of high tenacity and a copper spiral for electrostatic discharges. The exterior layer is resistant to weather, ozone and abrasion.

## APPLICATIONS

Ideal hose for pumping hydrocarbons with low aromatic content (50%), mineral oils and greases.

## TEMPERATURES

From -30°C to +80°C

ø Interior mm	ø Exterior mm	Weight kg/m	Working pressure bar	Burst pressure bar	Roll m	Code
12	24	0,35	15	45	61	AP930012024
13	25	0,37	15	45	61	AP930012025
15	26	0,40	15	45	61	AP930015026
16	27	0,42	15	45	61	AP930016027
19	30	0,55	15	45	61	AP930019030
22	34	0,70	15	45	61	AP930022034
25	37	0,80	15	45	61	AP930025037
28	40	0,90	15	45	61	AP930028040
30	42	0,96	15	45	61	AP930030042
32	44	1,00	15	45	61	AP930032044
35	47	1,25	15	45	61	AP930035047
38	50	1,40	15	45	61	AP930038050
40	54	1,50	15	45	61	AP930040054
42	56	1,65	15	45	61	AP930042056
45	60	1,74	15	45	61	AP930045060
48	63	1,80	15	45	61	AP930048063
51	66	1,90	15	45	61	AP930051066
55	70	2,00	15	45	40	AP930055070
60	75	2,10	15	45	40	AP930060075
63	79	2,15	15	45	40	AP930063079
65	79	2,20	15	45	40	AP930065081
70	84	2,30	15	45	40	AP930070086
76	92	2,50	15	45	20	AP930076092
80	96	2,80	15	45	20	AP930080096
85	99	3,00	15	45	20	AP930085099
90	106	3,20	15	45	20	AP930090106
102	118	3,40	15	45	20	AP930102117
110	128	3,45	15	45	20	AP930110125
120	140	3,70	15	45	20	AP930120140
127	147	4,00	15	45	20	AP930127144
152	176	5,00	15	45	10	AP930152172