

PVC-PU SUCTION



CHARACTERISTICS

Translucent hose made of polyurethane and reinforced with a rigid non-deformable PVC spiral. Non-toxic and suitable for food use. Smooth interior surface. High resistance to abrasion, atmospheric agents and various chemical products.

APPLICATIONS

Ideal hose for suction and pumping of abrasive materials (sand, grain, sawdust, etc.), ventilation and conduit for air, dust, gas, smoke and reactive substances. Suction of abrasive content food material that require simulants A, B, C and E under OM2 conditions according to EU / 10/2011 regulation (cereals, flours, etc).

TEMPERATURES

From -20°C to +80°C

ø Interior mm	Wall thickness mm	Flexible thickness mm	Curvature radius mm	Vacuum mH ₂ O	Roll m	Code
25	3,0	0,5	25	3	30	AF244025
30	3,0	0,5	30	3	30	AF244030
32	3,1	0,5	32	3	30	AF244032
35	3,1	0,5	35	3	30	AF244035
38	3,1	0,5	38	3	30	AF244038
40	3,1	0,5	40	3	30	AF244040
45	3,3	0,5	45	3	30	AF244045
50	3,3	0,5	50	3	30	AF244050
51	3,3	0,5	50	3	30	AF244051
60	3,4	0,5	60	3	30	AF244060
63	3,4	0,5	60	3	30	AF244063
70	3,5	0,5	70	3	30	AF244070
75	3,8	0,5	75	3	30	AF244075
80	3,9	0,5	80	3	30	AF244080
90	4,4	0,6	90	3	30	AF244090
102	4,5	0,6	100	3	30	AF244102
110	5,2	0,6	110	3	30	AF244110
120	5,2	0,6	120	3	30	AF244120
125	5,3	0,6	125	3	30	AF244125
130	5,3	0,6	130	3	30	AF244130
140	5,3	0,7	140	3	30	AF244140
150	5,6	0,7	150	3	30	AF244150
160	5,8	0,8	160	3	30	AF244160
170	5,8	0,8	170	3	30	AF244170
180	6,0	0,8	180	3	20	AF244180
200	6,5	1,0	200	3	20	AF244200
250	6,5	1,0	250	3	10	AF244250
300	6,8	1,0	300	3	10	AF244300