

SMS CONNECTORS

SMS stainless couplings are manufactured according to standard 1145, suitable for use in the food, chemical and pharmaceutical industries. The thread complies with DIN 405/1.

MATERIALS

SS316

SS304

SMS - MALE WELD



CODE FIC1611

ND

25

38

50

63

76

104

SMS- CAP WELD



CODE FIC1612

ND

25

38

50

63

76

104

SMS - CAP WITH GROOVED SHANK



CODE FIC1620

ND

25

32

38

51

63

76

104

Ø Espiga mm

25

32

38

51

63

76

100

SMS - CAP WITH GROOVED SHANK



CODE FIC1630

ND

25

32

38

51

63

76

104

Ø Shank mm

25

30

38

51

63

76

101

SMS - NUT



CODE FIC1603

ND

25

38

50

63

76

104

SMS - CAP NOTE WITH PIVOT



CODE FIC1623

ND

25

38

50

63

76

104

SMS - SEAL



CODE
EPDM FIC1608
NBR FIC1609
Viton FIC16010

ND

25

38

50

63

76

104

SMS - KEY



CODE CC600160

MATERIALS
Stainless steel

TECNIMAN

Camino del fus, 59 • 46470 Massanassa (Valencia - Spain)
P. +34 96 125 30 55 • Fax +34 96 125 00 45 • info@tecniman.es • www.tecniman.es