

SPRING-GASOIL



CHARACTERISTICS

Hose made of flexible PVC and polymeric plasticizers, reinforced with a spiral of galvanised steel. Smooth interior and exterior wall. High flexibility and non-toxic. Curvature radius 3xDi.

APPLICATIONS

Ideal hose for the suction and pumping of hydrocarbons: gasoline, fuel, oils and petroleum derivatives.

TEMPERATURES

From -20°C to +60°C

ø Interior mm	ø Exterior mm	Working pressure bar	Vacuum mH ₂ O	Roll m	Code
19	26	8	7,5	50	AE226019
20	27	8	7,5	50	AE226020
25	34	7,5	7	50	AE226025
30	39	7	6	50	AE226030
32	41	7	6	50	AE226032
35	45	6,5	6	50	AE226035
40	51	6	6	50	AE226040
45	57	5,5	6	50	AE226045
50	62	5	6	50	AE226050
55	68	4,5	6	50	AE226055
60	73	4,5	6	50	AE226060
63	76	4	5,5	50	AE226063
65	78	4	5	50	AE226065
70	84	4	5	50	AE226070
75	89	3,5	5	50	AE226075
80	94	2,5	5	50	AE226080
90	105	2	5	30	AE226090
100	117	2	5	30	AE226100