#### STEAM HOSE FITTINGS

The steam fittings are manufactured according to EN14423 for steam hoses with a working pressure of 18 bar. They withstand temperatures up to a maximum of 210°C for saturated steam and up to a maximum of 120°C for hot water.

# STEAM HOSE COUPLING MALE WITH MALE THREAD - STEEL



CODE CG53500

| ND mm | Male thread<br>inches |
|-------|-----------------------|
| 13    | 1/2"                  |
| 19    | 3/4"                  |
| 25    | 1″                    |
| 32    | 1″1/4                 |
| 38    | 1″1/2                 |
| 51    | 2"                    |
|       |                       |

Male thread

inches

1/2"

3/4"

1"

1″1/4

1″1/2

### STEAM HOSE COUPLING MALE WITH FEMALE THREAD - STEEL



CODE CG53510

CODE

| ND mm | Female thread inches |
|-------|----------------------|
| 13    | 1/2"                 |
| 19    | 3/4"                 |
| 25    | 1"                   |
| 32    | 1″1/4                |
| 38    | 1″1/2                |
| 51    | 2"                   |

### STEAM HOSE COUPLING MALE WITH MALE THREAD - AISI316

ND mm

13



25 32 38 CODE CG53501

### STEAM HOSE COUPLING MALE WITH FEMALE THREAD - AISI316



ND mm Female thread inches

13 1/2"
19 3/4"
25 1"
32 1"1/4
38 1"1/2
51 2"

# SWIVEL FLANGE FOR STEAM PN40 WITH COLLAR - STEEL



CODE CG53520 ø Shank 1/2" 3/4" 1" SWIVEL FLANGE FOR STEAM PN40 WITH COLLAR - AISI316



ø Shank 1/2" 3/4" 1" 2"

CODE CG53521

# DIN11851 STEAM HOSE, SERRATED HOSE SHANK AND SAFETY COLLAR WITH MALE THREAD - AISI 316



| ø Shank mm | Coupling |
|------------|----------|
| 19         | DN19     |
| 25         | DN25     |
| 32         | DN32     |
| 38         | DN40     |
| 50         | DN50     |

CODE CG53530

# DIN11851 STEAM HOSE, SERRATED HOSE SHANK AND SAFETY COLLAR WITH FEMALE THREAD - AISI 316



| ø Shank mm | Coupling |
|------------|----------|
| 19         | DN19     |
| 25         | DN25     |
| 32         | DN32     |
| 38         | DN40     |
| 50         | DN50     |
|            |          |

CODE CG53531

### STEAM HOSE COUPLING MALE WITH MALE THREAD - BRASS



| ND mm | Male thread inches |
|-------|--------------------|
| 13    | 1/2"               |
| 19    | 3/4"               |
| 25    | 1"                 |
| 32    | 1″1/4              |
| 38    | 1″1/2              |
| 51    | 2"                 |
|       |                    |

CODE CG53502

### STEAM HOSE COUPLING MALE WITH FEMALE THREAD - BRASS



| ND mm | Female thread inches |
|-------|----------------------|
| 13    | 1/2"                 |
| 19    | 3/4"                 |
| 25    | 1"                   |
| 32    | 1″1/4                |
| 38    | 1″1/2                |
| 51    | 2"                   |

CODE CG53512

### SAFETY CLAMP FOR STEAM HOSE COUPLINGS - AISI 304



| Hose mm | ND mm |
|---------|-------|
| 13x6    | 24-26 |
| 19x7    | 32-34 |
| 25x7,5  | 39-41 |
| 32x8    | 47-50 |
| 38x8    | 53-56 |
| 50x9    | 67-69 |

CODE CG53541

**MATERIALS** Screws in stainless steel

# SAFETY CLAMP FOR STEAM HOSE COUPLINGS - BRASS



| Hose mm | ND mm |
|---------|-------|
| 13x6    | 24-26 |
| 19x7    | 32-34 |
| 25x7,5  | 39-41 |
| 32x8    | 47-50 |
| 38x8    | 53-56 |
| 50x9    | 67-69 |

CODE CG53542

MATERIALS Screws in stainless steel

