

STORZ COUPLINGS

The Storz couplings are used for applications in hydrocarbons, powder products, irrigation with submersible pumps, motor pumps and fire protection applications with a nominal pressure of 12 bar.

MATERIALS

Forged aluminium

STORZ - HOSE



CODE CG272

Closure type	Ø Hose mm
25-D	19
25-D	25
52-C	25
52-C	32
52-C	38
52-C	45
52-C	52
75-B	65
75-B	70
75-B	75
110-A	100
110-A	110

STORZ - FEMALE THREAD



CODE CG274

Closure type	Female thread inches
25-D	3/4"
25-D	1"
52-C	1"
52-C	1" 1/4
52-C	1" 1/2
52-C	2"
52-C	2" 1/2
75-B	2"
75-B	2" 1/2
75-B	3"
110-A	4"

STORZ - MALE THREAD



CODE CG276

Closure type	Male thread inches
25-D	3/4"
25-D	1"
52-C	1"
52-C	1" 1/4
52-C	1" 1/2
52-C	2"
52-C	2" 1/2
75-B	2"
75-B	2" 1/2
75-B	3"
110-A	4"

STORZ - REDUCER



CODE CG280

Closure type	Closure type
52-C	25-D
75-B	52-C
110-A	52-C
110-A	75-B

STORZ - CAP WITH CHAIN



CODE CG278

Closure type
25-D
52-C
75-B
110-A

STORZ - SEALS



CODE
Black NBR DA282
White NBR DA283
Viton DA284
Silicone FDA DA285

MATERIALES Black NBR, white NBR, Viton, silicone FDA.

STORZ - WRENCH



CODE CG221133100

TECNIMAN

Camino del fus, 59 • 46470 Massanassa (Valencia - Spain)
P. +34 96 125 30 55 • Fax +34 96 125 00 45 • info@tecniman.es • www.tecniman.es