

6 BAR CEMENT PUMP

Abrasion-resistant hoses

CHARACTERISTICS

Hose constructed around a mandrel with an NR rubber interior which is conductive and abrasion-resistant. The outer layer is NR rubber which is abrasion and weather-resistant. It has an intertwined textile braid of high tenacity.

APPLICATIONS

Ideal hose for pumping cement in powder, concrete and granulated materials at low pressure.

TEMPERATURES

From -40°C to +70°C.



ø Interior mm.	ø Exterior mm.	Bar Pressure	Roll mts.	Code
50	62	6	61	AP9117902050
51	66	6	61	AP9117902051
60	76	6	40	AP9117902060
75	90	6	40	AP9117902075
75	93	6	40	AP9117902076
76	86	6	40	AP9117902077
80	92	6	40	AP9117902080
80	96	6	40	AP9117902081
80	98	6	40	AP9117902082
90	102	6	20/40	AP9117902090
90	106	6	20/40	AP9117902092
90	110	6	20/40	AP9117902093
102	114	6	20	AP9117902102
102	122	6	20	AP9117904104
110	126	6	20	AP9117904110
125	138	6	20	AP9117904125
152	168	6	20	AP9117904152

NOTE

Also available with white food NR rubber interior (Code AP920) and anti-abrasive for unloading granulated food products (flours, sugars, cereals...).