

FLAT SYNTHETIC

CHARACTERISTICS

Flat hose with exterior of white synthetic material and interior of rubber and synthetic materials. Very flexible. Exterior thread treated with an anti-damp system. Also, this thread contributes high abrasion-resistance to the hose.

APPLICATIONS

It is an ideal hose for completing fire protection kits, for fire stations and civil construction.

TEMPERATURES

From -30°C to +90°C.



ø Interior mm.	Thickness mm.	Bar Pressure	Roll mts.	Code
25	2,30	30	30-60	AQ270025
32	2,30	25	30-60	AQ270032
38	2,30	25	30-60	AQ270038
42	2,30	20	30-60	AQ270042
45	2,30	20	30-60	AQ270045
52	2,30	15	30-60	AQ270052
55	2,50	15	30-60	AQ270055
60	2,50	15	30-60	AQ270063
70	2,60	15	30-60	AQ270070
75	2,60	15	30-60	AQ270075
80	2,80	15	30-60	AQ270080
90	2,80	15	30-60	AQ270090
100	3,00	15	30-60	AQ270100
110	3,00	15	30-60	AQ270110
125	3,00	15	30-60	AQ270125
150	3,00	10	30-60	AQ270150
200	3,50	8	30-60	AQ270200