

ANTI-STATIC PVC-PU SUCTION



CHARACTERISTICS

Translucent hose made of polyurethane and reinforced with a non-deformable rigid PVC spiral and a copper thread that provides anti-static properties. The inner wall is smooth to avoid the formation of sediments. High resistance to abrasion, atmospheric agents and various chemical products. Non-toxic and for food use. Suitable for installations governed by ATEX regulations.

APPLICATIONS

Ideal hose for suction and pumping of abrasive materials (sand, grain, sawdust, etc.) and in abrasive conditions of use.

TEMPERATURES

From -20°C to +80°C

ø Interior mm	Wall thickness mm	Flexible thickness mm	Weight g/m	Vacuum mH ₂ O	Curvature radius mm	Roll m	Code
20	3,0	0,5	125	3	20	30	AF243020
22	3,0	0,5	136	3	22	30	AF243022
25	3,0	0,5	154	3	25	30	AF243025
30	3,0	0,5	170	3	30	30	AF243030
32	3,1	0,5	180	3	32	30	AF243032
35	3,1	0,5	195	3	35	30	AF243035
38	3,1	0,5	225	3	38	30	AF243038
40	3,1	0,5	250	3	40	30	AF243040
45	3,3	0,5	260	3	45	30	AF243045
50	3,3	0,5	300	3	50	30	AF243050
51	3,3	0,5	305	3	51	30	AF243051
60	3,4	0,5	425	3	60	30	AF243060
63	3,4	0,5	445	3	63	30	AF243063
70	3,5	0,5	500	3	70	30	AF243070
75	3,8	0,5	550	3	75	30	AF243075
80	3,9	0,5	590	3	80	30	AF243080
90	4,4	0,6	670	3	90	30	AF243090
102	4,5	0,6	870	3	102	30	AF243102
110	5,2	0,6	950	3	110	30	AF243110
120	5,2	0,6	1000	3	120	30	AF243120
125	5,3	0,6	1200	3	125	30	AF243125
140	5,3	0,7	1300	3	140	30	AF243140
150	5,3	0,7	1500	3	150	30	AF243150
160	5,6	0,8	1700	3	160	30	AF243160
170	5,8	0,8	1900	3	170	30	AF243170
180	5,8	0,8	1950	3	180	20	AF243180
200	6,0	1,0	2200	3	200	20	AF243200
250	6,5	1,0	2600	3	250	10	AF243250
300	6,8	1,0	3425	3	300	10	AF243300