

GLASS



CHARACTERISTICS

Hose made of laminated transparent PVC. High flexibility and permeability. Unlikely breakage when stretched out. High resistance to atmospheric agents.

APPLICATIONS

Ideal hose for the transport of liquids where visual control is required, levelling in construction and irrigation in general.

TEMPERATURES

From -10°C to +60°C

ø Interior mm	ø Exterior mm	Weight g/m	Curvature radius mm	Roll m	Code
2+/-0,3	4+/-0,3	12	8	50	AH026010204
3+/-0,3	5+/-0,3	16	10	50	AH026010305
4+/-0,3	6+/-0,3	20	12	50	AH026010406
5+/-0,3	7+/-0,3	24	15	50	AH026010507
5+/-0,3	8+/-0,3	39	16	50	AH026010508
6+/-0,3	8+/-0,3	28	16	50	AH026010608
6+/-0,3	9+/-0,3	45	18	50	AH026010609
6+/-0,3	10+/-0,3	62	20	50	AH026010610
6+/-0,3	12+/-0,3	104	25	50	AH026010612
7+/-0,3	10+/-0,3	49	20	50	AH026010710
8+/-0,3	10+/-0,3	35	20	50	AH026010810
8+/-0,3	11+/-0,3	55	25	50	AH026010811
8+/-0,3	12+/-0,3	78	25	50	AH026010812
8+/-0,3	14+/-0,3	128	30	50	AH026010814
9+/-0,3	12+/-0,3	61	25	50	AH026010912
9+/-0,3	13+/-0,3	85	30	50	AH026010913
9+/-0,3	15+/-0,3	140	35	50	AH026010915
10+/-0,3	12+/-0,3	43	25	50	AH026011012
10+/-0,3	13+/-0,3	67	30	50	AH026011013
10+/-0,3	14+/-0,3	93	35	50	AH026011014
12+/-0,3	15+/-0,3	78	35	50	AH026011215
12+/-0,3	16+/-0,3	108	35	50	AH026011216
12+/-0,3	18+/-0,3	174	35	50	AH026011218
13+/-0,3	19+/-0,3	186	40	50	AH026011319
14+/-0,3	18+/-0,3	124	40	50	AH026011418
15+/-0,3	20+/-0,3	169	45	50	AH026011520
18+/-0,3	23+/-0,3	198	50	50	AH026011823
20+/-0,3	25+/-0,3	218	50	50	AH026012025
25+/-0,3	31+/-0,3	325	60	50	AH026012531
30+/-0,3	38+/-0,3	526	75	50	AH026013038
35+/-0,3	43+/-0,3	603	85	50	AH026013543
40+/-0,3	49+/-0,3	775	100	25	AH026014049
50+/-0,3	60+/-0,3	1065	120	25	AH026015060