

# PVC SANITATION

Hoses for liquids



## CHARACTERISTICS

Hose made of flexible PVC and reinforced with a rigid non-deformable PVC spiral. Smooth interior and exterior wall. Exterior diameters adjusted to facilitate assembly with PVC accessories. High resistance to waste water and to a wide range of chemical products. Available in grey and white. Curvature radius 3xDi.

## APPLICATIONS

Ideal hose for drains of air conditioning and bathroom devices, as well as pump facilities in swimming pools.

## TEMPERATURES

From -10°C to +60°C.

| ø Interior mm | ø Exterior mm | Weight g/m | Vacuum mH <sub>2</sub> O | Work pressure bar | Burst pressure bar | Curvature radius mm | Roll m | Code      |
|---------------|---------------|------------|--------------------------|-------------------|--------------------|---------------------|--------|-----------|
| 13            | 16            | 100        | 7                        | 7                 | 22                 | 39                  | 25/50  | AT500013  |
| 16            | 20            | 155        | 7                        | 7                 | 22                 | 48                  | 25/50  | AT500016  |
| 20            | 25            | 240        | 7                        | 7                 | 22                 | 60                  | 25/50  | AT500020  |
| 25            | 32            | 400        | 7                        | 7                 | 22                 | 75                  | 25/50  | AT500025  |
| 26            | 32            | 370        | 7                        | 5                 | 16                 | 78                  | 25/50  | AT500026  |
| 27            | 32            | 334        | 7                        | 5                 | 16                 | 81                  | 25/50  | AT500027  |
| 34            | 40            | 480        | 7                        | 5                 | 16                 | 102                 | 25/50  | AT500034  |
| 35            | 40            | 400        | 7                        | 5                 | 16                 | 105                 | 25/50  | AT500035  |
| 42            | 50            | 710        | 7                        | 5                 | 16                 | 126                 | 25/50  | AT500042  |
| 43            | 49            | 550        | 7                        | 5                 | 16                 | 129                 | 25/50  | AT500043  |
| 43            | 50            | 685        | 7                        | 5                 | 16                 | 129                 | 25/50  | AT5000430 |
| 55            | 63            | 1000       | 7                        | 5                 | 16                 | 165                 | 25/50  | AT500055  |
| 65            | 75            | 1400       | 7                        | 4                 | 12,5               | 195                 | 25/50  | AT500065  |
| 80            | 90            | 1800       | 7                        | 4                 | 12,5               | 240                 | 25/50  | AT500080  |
| 100           | 110           | 2200       | 7                        | 3                 | 9,5                | 300                 | 25/50  | AT500100  |
| 110           | 125           | 3700       | 7                        | 3                 | 9,5                | 330                 | 25/50  | AT500110  |