

# REINFORCED GLASS



## CHARACTERISTICS

Hose made of laminated transparent PVC and reinforced with polyester mesh to resist high pressures. High flexibility. Unlikely constriction and breakage in elongation. Resistant to atmospheric agents and chemical products. Non-toxic and for food use (except fatty foods).

## APPLICATIONS

Ideal hose for multiple applications, mainly agriculture, industry and construction. Suitable for the passage of food liquids, air and compressed air. Phthalate free.

## TEMPERATURES

From -10°C to +60°C.

| ø Interior mm | ø Exterior mm | Weight g/m | Working pressure bar | Burst pressure bar | Curvature radius mm | Roll m | Code     |
|---------------|---------------|------------|----------------------|--------------------|---------------------|--------|----------|
| 6             | 12            | 110        | 15                   | 45                 | 15                  | 50     | AN171006 |
| 8             | 14            | 130        | 15                   | 45                 | 25                  | 50     | AN171008 |
| 10            | 16            | 155        | 15                   | 45                 | 30                  | 50     | AN171010 |
| 12            | 18            | 180        | 15                   | 45                 | 35                  | 50     | AN171013 |
| 13            | 19            | 195        | 15                   | 45                 | 40                  | 50     | AN171014 |
| 16            | 22            | 225        | 15                   | 45                 | 60                  | 50     | AN171016 |
| 19            | 25            | 260        | 10                   | 30                 | 75                  | 50     | AN171019 |
| 25            | 32            | 390        | 10                   | 30                 | 110                 | 50     | AN171025 |
| 30            | 38            | 530        | 7                    | 21                 | 160                 | 50     | AN171030 |
| 32            | 38            | 406        | 7                    | 21                 | 160                 | 50     | AN171032 |
| 38            | 48            | 835        | 6                    | 18                 | 225                 | 50     | AN171038 |
| 50            | 60            | 1075       | 5                    | 15                 | 290                 | 50     | AN171050 |