

RUBBER BARS AND CORDS

SILICONE BAR



CODE BN029

Bar made of silicone, non-toxic and suitable for food use. High resistance to temperature.

TEMPERATURE -50°C a +200°C
HARDNESS 60 SH

WIDTH
Bajo demanda

THICKNESS
De 3 mm a 30 mm

SILICONE BAR



CODE BN190

Cord made of silicone, non-toxic and suitable for food use. High resistance to temperature.

TEMPERATURE -50°C a +200°C
HARDNESS 60 SH

DIAMETERS
De 1,5 mm a 30 mm

GREY BAR



CODE BC207

Bar made of spongy rubber in grey colour. Ideal for sealing hatches, tanks and isolation in general.

TEMPERATURE -40°C a +70°C
HARDNESS 25 SH

WIDTH
De 10 mm a 100 mm

THICKNESS
De 2 mm a 30 mm

ADH RUBBER BAR



CODE BC21506

Bar which is adhesive on one side, made of black spongy rubber. Ideal for sealing, tanks and isolation in general.

TEMPERATURE -40°C a +70°C
HARDNESS 25 SH

WIDTH
De 10 mm a 100 mm

THICKNESS
De 2 mm a 30 mm

NEOPRENE SPONGE CORD



CODE BC520

Cord of spongy neoprene rubber, ideal for watertight seals.

Diameter mm	Roll m
3	750
4	1000
5	750
6	500
7	500
8	300
10	50
12	50
15	50
20	25
25	25

TEMPERATURE
-40°C a +80°C
HARDNESS 25 SH

NBR CORD



CODE BN150

Cord of nitrile rubber, ideal for watertight seals where resistance to oils or gasoline is required.

Diameter mm	Roll m
4	100
6	100
7	100
8	100
10	100
12	50
15	50
20	25

TEMPERATURE
-40°C a +110°C
HARDNESS 60 SH