

WATERPROOFING

WAX PAPER




CODE BE410

Sheet of wax paper in brown colour, ideal for the manufacture of seals.

TEMPERATURE +120°C
THICKNESS De 0,2 a 3 mm
ROLL WIDTH 1000 mm

ECO200 SHEET



CODE BE311001

Compressed fibreboard sheet in green colour, ideal for the manufacture of seals, free from asbestos, resistant to high temperatures and to a working temperature of 40 bars.

TEMPERATURE +180°C
THICKNESS De 0,5 a 5 mm
DIMENSIONS 1350x1500 mm

GRAPHITE SHEET



CODE BE311004

Compressed fibreboard sheet in black colour with graphite finish, ideal for manufacturing seals, free from asbestos, resistant to high temperatures and to a working pressure of 80 bars.

TEMPERATURE +350°C
THICKNESS De 0,5 a 5 mm
DIMENSIONS 1350x1500 mm

FLAT SEAL FOR FEMALE THREAD



CODE
ECO-200 RG1480
NBR RG1481
EPDM RG149
PTFE DA723

Diámetro mm

1/2"

3/4"

1"

1" 1/4

1" 1/2

2"

3"

4"

FIBREGLASS CORD



CODE BD101

TEMPERATURE
+600°C

Cord with fibreglass braid, treated for high temperatures. Supplied in full rolls.

Diameter mm

3

4

5

6

8

10

12

14

16

20

FIBREGLASS TAPE



CODE BD104

TEMPERATURA
+600°C

Braided fibreglass tape, treated for high temperatures. Supplied in full rolls.

Width mm

20

30

40

50

60

70

80

90

100

120

150

200

TECNIMAN

Camino del fus, 59 • 46470 Massanassa (Valencia - Spain)

P. +34 96 125 30 55 • Fax +34 96 125 00 45 • info@tecniman.es • www.tecniman.es