

# INDUSTRIAL SUCTION

Hoses for aeration



## CHARACTERISTICS

Grey hose made of EVA. Very resistant to permanent deformations. Resistant to UVA rays, cold and breakage along its length. Curvature radius 1xDi.

## APPLICATIONS

Ideal hose for the suction of air, dust, welding smoke and exhaust fumes (unloading). Industrial suction.

## TEMPERATURES

From -30°C to +60°C.

| ø Interior mm. | ø Exterior mm. | Empty mH <sub>2</sub> O | Roll mts. | Code     |
|----------------|----------------|-------------------------|-----------|----------|
| 20+/-1,25      | 28             | 5                       | 30        | AT450020 |
| 25+/-1,25      | 33             | 5                       | 30        | AT450025 |
| 28+/-1,25      | 35             | 5                       | 30        | AT450028 |
| 30+/-1,25      | 39             | 5                       | 30        | AT450030 |
| 32+/-1,25      | 41             | 5                       | 30        | AT450032 |
| 35+/-1,50      | 44             | 5                       | 30        | AT450035 |
| 38+/-1,50      | 48             | 5                       | 30        | AT450038 |
| 40+/-1,50      | 50             | 5                       | 30        | AT450040 |
| 45+/-1,50      | 55             | 5                       | 30        | AT450045 |
| 50+/-1,50      | 61             | 4                       | 30        | AT450050 |
| 60+/-1,50      | 72             | 4                       | 30        | AT450060 |

**NOTE** Black color available on request (Code AT440).