

HYDROCARBON SUCTION 10 BAR



CHARACTERISTICS

Hose of black NBR rubber constructed around a mandrel with intertwined textile reinforcement of high tenacity and steel spiral. The exterior layer is conductive and resistant to weather, ozone and abrasion

APPLICATIONS

Ideal hose for the pumping and suction of hydrocarbons with low aromatic content (50% max.) and oleodynamic oil in return circuits.

TEMPERATURES

From -20°C to +100°C.

ø Interior mm	ø Exterior mm	Weight kg/m	Working pressure bar	Burst pressure bar	Depressure bar	Curvature radius mm	Roll m	Code
19	29	0,60	10	30	0,8	115	61	AP931019029
25	35	0,75	10	30	0,8	150	61	AP931025035
28	38	0,80	10	30	0,8	170	61	AP931028038
30	40	0,90	10	30	0,8	180	61	AP931030040
32	42	0,95	10	30	0,8	190	61	AP931032042
35	45	1,05	10	30	0,8	210	61	AP931035046
38	48	1,10	10	30	0,8	230	61	AP931038049
40	50	1,20	10	30	0,8	240	61	AP931040050
42	52	1,20	10	30	0,8	255	61	AP931042052
45	55	1,25	10	30	0,8	270	61	AP931045056
48	58	1,30	10	30	0,8	285	61	AP931048058
51	61	1,40	10	30	0,8	300	61	AP931051061
51	63	1,55	10	30	0,8	310	61	AP931051063
60	71	1,95	10	30	0,8	360	40	AP931060071
60	74	2,00	10	30	0,8	380	40	AP931060074
63	74	2,05	10	30	0,8	390	40	AP931063077
65	77	2,20	10	30	0,8	410	40	AP931065079
70	82	2,35	10	30	0,8	420	20	AP931070085
76	88	2,55	10	30	0,8	450	20	AP931076090
80	94	2,80	10	30	0,8	480	20	AP931080095
85	99	3,20	10	30	0,8	510	20	AP931085099
90	104	3,50	10	30	0,8	540	20	AP931090104
102	118	4,40	10	30	0,8	600	20	AP931102117
127	147	6,85	10	30	0,8	700	20	AP931127147
152	168	7,90	10	30	0,8	900	20	AP931150168