MILK SEMI-CORRUGATED BUTYL



CHARACTERISTICS

Hose constructed around a mandrel with an interior of white non-toxic butyl rubber and exterior of blue semi-corrugated food quality rubber which is abrasion resistant. Intertwined textile reinforcement of high tenacity and double steel spiral.

APPLICATIONS

Ideal hose for suction and pumping of multiple food fluids such as wine, beer, mineral water, high alcohol content drinks (max. 92%), fruit juices, milk and derivatives. Complies with FDA and BFR food standards. Free of phthalates.

TEMPERATURES

From -20°C to +100°C. Steam wash at 130°C during 30 min. Maximum peaks of 150°C.

ı	ø Interior mm	Working pressure bar	Curvature radius mm	Roll m	Code
	19	10	48	40	AP956000019
	25	10	63	40	AP956000025
	32	10	80	40	AP956000032
	38	10	95	40	AP956000037
	40	10	95	40	AP956000038
	51	10	125	40	AP956000050
	60	10	160	40	AP956000060
	63	10	160	40	AP956000063
	76	10	190	20	AP956000076
	80	10	190	20	AP956000080
	102	10	300	20	AP956000102

CNI , AN

ECNI , AN

ECNI AN

ECNI AN

ECNI A

CNI AN

ECKI AN

FCN AX

ECNI AN

CNI, AN

ECNI, AN

ECNI AN

ECNI AN

ECNI', AN

CNI', AN

ECNI AN

ECNI . AN

ECNI . AN

ECNI AN







