

MULTIFLEX



CHARACTERISTICS

Hose constructed around a mandrel, with interior of NBR rubber and conductor. The exterior layer is of semi-corrugated NRB rubber, conductive and weather and abrasion resistant. Flame resistant according to TRbF 131 Teil 2-5.5. It has an intertwined textile reinforcement of high tenacity and a spiral of helical steel.

APPLICATIONS

Ideal hose for pumping and suction at 13 bar pressure of multiple applications with hot water up to 120°C and hydrocarbons with maximum aromatic content of 40% or oleodynamic oil in return circuits up to 100°C.

TEMPERATURES

From -20°C to +120°C.

Ø Interior mm	Working pressure bar	Vacuum bar	Roll m	Code
19	13	0,8	61	AP965019
25	13	0,8	61	AP965025
30	13	0,8	61	AP965030
32	13	0,8	61	AP965032
35	13	0,8	61	AP965035
38	13	0,8	61	AP965038
40	13	0,8	61	AP965040
42	13	0,8	61	AP965042
45	13	0,8	61	AP965045
48	13	0,8	61	AP965048
51	13	0,8	61	AP965051
60	13	0,8	61	AP965060
63	13	0,8	61	AP965063
70	13	0,8	61	AP965070
76	13	0,8	61	AP965076
80	13	0,8	61	AP965080
102	13	0,8	40	AP965102