

PUMPING MORTAR 40 BAR



CHARACTERISTICS

APPLICATIONS

TEMPERATURES

Hose constructed around a mandrel with a conductive NR rubber interior and resistance to abrasion. The outer layer is NR rubber which is abrasion and weather-resistant. It has a textile braid of high tenacity intertwined inside.

Ideal hose for pumping cement mortar, gypsum and shotcrete processes in general (wet abrasion).

From -40°C to +70°C.

ø Interior mm	ø Exterior mm	Weight kg/m	Working pressure bar	Burst pressure bar	Roll m	Code
25	37	0,80	40	105	61	AP9400025
28	41	0,95	40	105	61	AP9400027
32	46	1,10	40	105	61	AP9400032
35	49	1,15	40	105	61	AP9400035
35	55	1,50	40	105	61	AP9400036
38	54	1,40	40	105	61	AP9400038
40	54	1,45	40	105	61	AP9400040
40	60	1,90	40	105	61	AP9400042
50	66	1,80	40	105	40	AP9400050
50	70	1,95	40	105	40	AP9400051
51	67	2,20	40	105	40	AP9400052
60	78	2,55	40	105	40	AP9400060
65	85	2,85	40	105	40	AP9400065
70	90	3,00	40	105	40	AP9400070
75	98	3,40	40	105	40	AP9400076