

SEMI-WAVY CHEMICAL UPE 16 BAR

Hoses



CHARACTERISTICS

Hose constructed around a mandrel, with black food quality UPE rubber interior resistant to abrasion. The exterior layer is of black EPDM rubber which is weather and abrasion resistant. It has an intertwined textile reinforcement of high tenacity and a spiral of helical steel.

APPLICATIONS

Food hose ideal for suction and pumping of chemical products. Particularly recommended for conduit of acids, bases, alkali, solvents, ketones, aldehydes, esters, alcohols and aromatics, aliphatics and chlorinated hydrocarbons. Also recommended for food and alcoholic drinks, cosmetic and pharmaceutical products. Complies with FDA food standards. High conductivity, suitable for environments and ATEX areas according with official report DEKRA 16EXAM11132 BVS-bk: area 0,1 and 2. It complies with regulation 12115.

TEMPERATURES

From -20°C to +70°C. Peaks of 130°C at 30 min. maximum.

ø Interior mm	ø Exterior mm	Working pressure bar	Roll m	Code
19	31	16	61	AP960S019031
25	37	16	61	AP960S025037
32	44	16	61	AP960S032044
38	51	16	61	AP960S038051
51	64	16	40	AP960S051066
63	78	16	40	AP960S063078
76	92	16	20	AP960S076092
100	116	16	20	AP960S100116