

TRANSFOR



CHARACTERISTICS

Gray hose made of flexible PVC and reinforced with non-deformable rigid PVC spiral. The inside wall of the tube is smooth, preventing sediment formation and facilitating tube sterilisation. Non-toxic but not for use with food. Good resistance to suction, impulsion, abrasion atmospheric agents and various chemical products. Radius of curvature 5xDi.

APPLICATIONS

Ideal hose for suction and discharge pumping. Transport of aggressive liquids by pumping (cesspools, sewers, chemical products, etc.) and where high resistance to pressure and vacuum is required.

TEMPERATURES

From -10°C to +60°C.

ø Interior mm	Wall thickness mm	Weight g/m	Working pressure bar	Burst pressure bar	Curvature radius mm	Vacuum mH ₂ O	Roll m	Code
30	5	635	5	15	150	9	50	AD206030
32	5	670	5	15	160	9	50	AD206032
35	5	675	5	15	175	9	50	AD206035
38	5	725	5	15	200	9	50	AD206038
40	5	765	5	15	200	9	50	AD206040
42	5	800	5	15	225	9	50	AD206042
45	5,5	900	5	15	250	9	50	AD206045
50	5,5	1080	5	15	275	9	50	AD206050
55	5,5	1440	5	15	300	9	50	AD206055
60	6,2	1500	5	15	315	9	50	AD206060
63	6,2	1550	5	15	325	9	50	AD206063
65	6,2	1650	5	15	350	9	50	AD206065
70	6,5	1800	5	15	375	9	50	AD206070
75	6,5	1980	5	15	400	9	50	AD206075
80	6,5	2340	4	12	450	9	50	AD206080
90	7,0	2970	4	12	500	9	30	AD206090
100	7,5	2970	3	9	500	9	30	AD206100
102	7,5	3110	3	9	500	9	30	AD206102
105	7,5	3240	3	9	550	9	30	AD206105
110	7,5	3500	3	9	600	9	30	AD206110
120	7,5	3600	3	9	625	9	20	AD206120
130	7,5	3750	3	9	650	9	20	AD206130
140	7,5	5300	3	9	700	9	20	AD206140
150	9,5	5670	3	9	750	9	5	AD206150
160	9,5	6000	3	9	800	9	5	AD206160
200	11,5	9250	2,5	7,5	1000	9	5	AD206200
250	12,5	11700	2,5	7,5	1250	9	5	AD206250
300	12,5	13500	2,5	7,5	1500	9	5	AD206300