

WATER SUCTION 10 BAR



CHARACTERISTICS

Black SBR rubber hose constructed around a mandrel with intertwined textile reinforcement of high tenacity and steel spiral. Weather, ozone and abrasion resistant.

APPLICATIONS

Ideal hose for suction and pumping of water, waste liquids and other inert solutions.

TEMPERATURES

From -20°C to +70°C.

ø Interior mm	ø Exterior mm	Weight kg/m	Working pressure bar	Curvature radius mm	Vacuum bar	Roll m	Code
19	29	0.60	10	110	0,8	61	AP903019029
25	35	0.75	10	150	0,8	61	AP903025035
30	40	0.90	10	180	0,8	61	AP903030040
32	42	0.95	10	200	0,8	61	AP903032042
35	45	1.00	10	210	0,8	61	AP903035045
38	48	1.10	10	230	0,8	61	AP903038048
40	50	1.15	10	240	0,8	61	AP903040050
45	55	1.25	10	270	0,8	61	AP903045055
51	61	1.40	10	300	0,8	61	AP903051061
60	71	1.95	10	360	0,8	61	AP903060070
63	74	2.05	10	390	0,8	20/40	AP903063074
70	82	2.50	10	420	0,8	20/40	AP903070082
76	88	2.90	10	450	0,8	20/40	AP903076088
80	92	3.40	10	480	0,8	20/40	AP903080092
90	103	3.80	10	540	0,8	20/40	AP903090102
102	116	4.40	10	610	0,8	20/40	AP903102115
110	124	4.70	10	660	0,8	20/40	AP903110124
127	142	5.30	10	770	0,8	20/40	AP903127140
152	169	6.20	5	650	0,8	20	AP903152169